

Package ‘ncar’

March 13, 2017

Version 0.3.3

Date 2017-03-12

Title Noncompartmental Analysis for Pharmacokinetic Data for Report

Description Conduct a noncompartmental analysis as closely as possible to the most widely used commercial software for pharmacokinetic analysis, i.e. 'Phoenix(R) WinNonlin(R)' <<https://www.certara.com/software/pkpd-modeling-and-simulation/phoenix-winnonlin/>>.

Some features are

- 1) CDISC SDTM terms
- 2) Automatic slope selection with the same criterion of WinNonlin(R)
- 3) Supporting both 'linear-up linear-down' and 'linear-up log-down' method
- 4) Interval(partial) AUCs with 'linear' or 'log' interpolation method
- 5) Produce pdf, rtf, text report files.

* Reference: Gabrielsson J, Weiner D. Pharmacokinetic and Pharmacodynamic Data Analysis - Concepts and Applications. 5th ed. 2016. (ISBN:9198299107).

Depends R (>= 2.0.0), rtf

Author Kyun-Seop Bae [aut]

Maintainer Kyun-Seop Bae <k@acr.kr>

Copyright 2016-2017, Kyun-Seop Bae

License GPL-3

NeedsCompilation no

LazyLoad yes

Repository CRAN

URL <https://cran.r-project.org/package=ncar>

Date/Publication

R topics documented:

ncar-package	2
AUC	3
BestSlope	4
IntAUC	5
Interpol	6
LinAUC	7
LogAUC	8
pdfNCA	9

Round	10
RptCfg	11
rtfNCA	12
Slope	13
sNCA	14
tabNCA	17
txtNCA	18
Unit	19
Index	21

ncar-package	<i>Noncompartmental Analysis for Pharmacokinetic Data for Reviewer</i>
--------------	--

Description

It conducts a noncompartmental analysis(NCA) as closely as possible to the most widely used commercial pharmacokinetic analysis software.

Details

The main functions are

NCA to perform NCA for many subjects.

IndiNCA to perform NCA for one subject.

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

1. Gabrielsson J, Weiner D. Pharmacokinetic and Pharmacodynamic Data Analysis - Concepts and Applications. 5th ed. 2016.
2. Shargel L, Yu A. Applied Biopharmaceutics and Pharmacokinetics. 7th ed. 2015.
3. Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics - Concepts and Applications. 4th ed. 2011.
4. Gibaldi M, Perrier D. Pharmacokinetics. 2nd ed. revised and expanded. 1982.

Examples

```
# Theoph and Indometh data: dose in mg, conc in mg/L, time in h
tabNCA(Theoph, dose=320, concUnit="mg/L")
tabNCA(Indometh, colSubj="Subject", colTime="time", colConc="conc", dose=25,
      adm="Infusion", dur=0.5, concUnit="mg/L")

tabNCA(Theoph, dose=320, concUnit="mg/L")
tabNCA(Indometh, colSubj="Subject", colTime="time", colConc="conc", dose=25,
      adm="Infusion", dur=0.5, concUnit="mg/L")

# Output to PDF file
pdfNCA(fileName="NCA-Theoph.pdf", Theoph, colSubj="Subject", colTime="Time",
```

```

colConc="conc", dose=320, doseUnit="mg", timeUnit="h", concUnit="mg/L")
pdfNCA(fileName="NCA-Indometh.pdf", Indometh, colSubj="Subject", colTime="time",
colConc="conc", adm="Infusion", dur=0.5, dose=25, doseUnit="mg",
timeUnit="h", concUnit="mg/L")

# Output to RTF file
rtfNCA(fileName="NCA-Theoph.rtf", Theoph, colSubj="Subject", colTime="Time",
colConc="conc", dose=320, doseUnit="mg", timeUnit="h", concUnit="mg/L")
rtfNCA(fileName="NCA-Indometh.rtf", Indometh, colSubj="Subject", colTime="time",
colConc="conc", adm="Infusion", dur=0.5, dose=25, doseUnit="mg",
timeUnit="h", concUnit="mg/L")

# For one subject
iAUC = data.frame(Name=c("AUC[0-12h]", "AUC[0-24h]"), Start=c(0,0), End=c(12,24)) ; iAUC

x = Theoph[Theoph$Subject=="1", "Time"]
y = Theoph[Theoph$Subject=="1", "conc"]

sNCA(x, y, dose=320, doseUnit="mg", concUnit="mg/L", timeUnit="h", iAUC=iAUC)
sNCA(x, y, dose=320, concUnit="mg/L", returnNA=FALSE, iAUC=iAUC)

txtNCA(x, y, dose=320, doseUnit="mg", concUnit="mg/L", timeUnit="h", iAUC=iAUC)

```

AUC

Calculate Area Under the Curve (AUC) and Area Under the first Moment Curve (AUMC) in a table format

Description

Calculate Area Under the Curve(AUC) and the first Moment Curve(AUMC) in two ways; 'linear trapezoidal method' or 'linear-up and log-down' method. Return a table of cumulative values.

Usage

```
AUC(x, y, down = "Linear")
```

Arguments

x	vector values of independent variable, usually time
y	vector values of dependent variable, usually concentration
down	either of "Linear" or "Log" to indicate the way to calculate AUC and AUMC

Details

fit="Linear" means linear trapezoidal rule with linear interpolation. fit="Log" means linear-up and log-down method.

Value

Table with two columns, AUC and AUMC; the first column values are cumulative AUCs and the second column values cumulative AUMCs.

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics - Concepts and Applications. 4th ed. pp687-689. 2011.

See Also

[LinAUC, LogAUC](#)

Examples

```
AUC(Theoph[Theoph$Subject==1, "Time"], Theoph[Theoph$Subject==1, "conc"]) # Default is "Linear"
AUC(Theoph[Theoph$Subject==1, "Time"], Theoph[Theoph$Subject==1, "conc"], down="Log")
```

BestSlope

Choose best fit slope for the log(y) and x regression by the criteria of adjusted R-square

Description

It sequentially fits ($\log(y) \sim x$) from the last point of x to the previous points with at least 3 points. It chooses a slope the highest adjusted R-square. If the difference is less than $1e-4$, it chooses longer slope.

Usage

```
BestSlope(x, y, adm = "Extravascular")
```

Arguments

x	vector values of x-axis, usually time
y	vector values of y-axis, usually concentration
adm	one of "Bolus" or "Infusion" or "Extravascular" to indicate drug administration mode

Details

Choosing the best terminal slope (y in log scale) in pharmacokinetic analysis is somewhat challenging, and it could vary by analysis performer. Currently this function uses ordinary least square method(OLS) only.

Value

R2	R-squared
R2ADJ	adjusted R-squared
LAMZNPT	number of points used for slope
LAMZ	negative of slope, lambda_z
b0	intercept of regression line
CORRXY	correlation of log(y) and x
LAMZLL	earliest x for lambda_z
LAMZUL	last x for lambda_z
CLSTP	predicted y value at last point, predicted concentration for the last time point

Author(s)

Kyun-Seop Bae <k@acr.kr>

See Also

[Slope](#)

Examples

```
BestSlope(Theoph[Theoph$Subject==1, "Time"],Theoph[Theoph$Subject==1, "conc"])
BestSlope(Indometh[Indometh$Subject==1, "time"],Indometh[Indometh$Subject==1, "conc"],
          adm="Bolus")
```

IntAUC	<i>Calculate interval AUC</i>
--------	-------------------------------

Description

It calculates interval AUC

Usage

```
IntAUC(x, y, t1, t2, Res, down = "Linear")
```

Arguments

x	vector values of independent variable, usually time
y	vector values of dependent variable, usually concentration
t1	start time for AUC
t2	end time for AUC
Res	result from IndiNCA function
down	either of "Linear" or "Log" to indicate the way to calculate AUC

Details

This calculates an interval (partial) AUC (from t1 to t2) with the given series of x and y. If t1 and/or t2 cannot be found within x vector, it interpolates according to the Method.

Value

return interval AUC value (scalar)

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

1. Gabrielsson J, Weiner D. Pharmacokinetic and Pharmacodynamic Data Analysis - Concepts and Applications. 5th ed. 2016.
2. Shargel L, Yu A. Applied Biopharmaceutics and Pharmacokinetics. 7th ed. 2015.
3. Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics - Concepts and Applications. 4th ed. 2011.
4. Gibaldi M, Perrier D. Pharmacokinetics. 2nd ed. revised and expanded. 1982.

See Also

[AUC](#), [Interpol](#)

Examples

```
Res = sNCA(Theoph[Theoph$Subject==1,"Time"], Theoph[Theoph$Subject==1, "conc"],
           dose=320, concUnit="mg/L")
IntAUC(Theoph[Theoph$Subject==1, "Time"], Theoph[Theoph$Subject==1, "conc"], t1=0.5, t2=11, Res)
```

Interpol

Interpolate y value

Description

It interpolates y value when a corresponding x value (xnew) does not exist within x vector

Usage

```
Interpol(x, y, xnew, Slope, b0, down = "Linear")
```

Arguments

x	vector values of x-axis, usually time
y	vector values of y-axis, usually concentration
xnew	new x point to be interpolated, usually new time point
Slope	slope of regression $\log(y) \sim x$
b0	y value of just left point of xnew
down	either of "Linear" or "Log" to indicate the way to interpolate

Details

This function interpolate y value, if xnew is not in x vector. If xnew is in x vector, it just returns the given x and y vector. This function usually is called by IntAUC function Returned vector is sorted in the order of increasing x values.

Value

new x and y vector containing xnew and ynew point

Author(s)

Kyun-Seop Bae <k@acr.kr>

See Also

[IntAUC](#)

Examples

```
x = 10:1 + 0.1
y = -2*x + 40.2
Interpol(x, y, 1.5)
Interpol(x, y, 1.5, down="Log")
```

LinAUC	<i>Area Under the Curve(AUC) and Area Under the first Moment Curve(AUMC) by linear trapezoidal method</i>
--------	---

Description

It calculates AUC and AUMC using linear trapezoidal method

Usage

```
LinAUC(x, y)
```

Arguments

x	vector values of independent variable, usually time
y	vector values of dependent variable, usually concentration

Details

This function returns AUC and AUMC by linear trapezoidal method.

Value

AUC	area under the curve
AUMC	area under the first moment curve

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

1. Gabrielsson J, Weiner D. Pharmacokinetic and Pharmacodynamic Data Analysis - Concepts and Applications. 5th ed. 2016.
2. Shargel L, Yu A. Applied Biopharmaceutics and Pharmacokinetics. 7th ed. 2015.
3. Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics - Concepts and Applications. 4th ed. 2011.
4. Gibaldi M, Perrier D. Pharmacokinetics. 2nd ed. revised and expanded. 1982.

See Also

[LogAUC,AUC](#)

Examples

```
LinAUC(Theoph[Theoph$Subject==1, "Time"],Theoph[Theoph$Subject==1, "conc"])
AUC(Theoph[Theoph$Subject==1, "Time"],Theoph[Theoph$Subject==1, "conc"]) # compare the last line
```

LogAUC	<i>Area Under the Curve(AUC) and Area Under the first Moment Curve(AUMC) by linear-up log-down method</i>
--------	---

Description

It calculates AUC and AUMC using linear-up log-down method

Usage

```
LogAUC(x, y)
```

Arguments

x	vector values of independent variable, usually time
y	vector values of dependent variable, usually concentration

Details

This function returns AUC and AUMC by linear-up log-down method.

Value

AUC	area under the curve
AUMC	area under the first moment curve

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

1. Gabrielsson J, Weiner D. Pharmacokinetic and Pharmacodynamic Data Analysis - Concepts and Applications. 5th ed. 2016.
2. Shargel L, Yu A. Applied Biopharmaceutics and Pharmacokinetics. 7th ed. 2015.
3. Rowland M, Tozer TN. Clinical Pharmacokinetics and Pharmacodynamics - Concepts and Applications. 4th ed. 2011.
4. Gibaldi M, Perrier D. Pharmacokinetics. 2nd ed. revised and expanded. 1982.

See Also

[LinAUC,AUC](#)

Examples

```
LogAUC(Theoph[Theoph$Subject==1, "Time"],Theoph[Theoph$Subject==1, "conc"])
# Compare the last line with the above
AUC(Theoph[Theoph$Subject==1, "Time"],Theoph[Theoph$Subject==1, "conc"], down="Log")
```

pdfNCA	<i>NCA output to pdf file</i>
--------	-------------------------------

Description

This output NCA result in a pdf file.

Usage

```
pdfNCA(fileName = "Temp-NCA.pdf", concData, colSubj = "Subject", colTime = "Time",
        colConc = "conc", dose = 0, adm = "Extravascular", dur = 0, doseUnit = "mg",
        timeUnit = "h", concUnit = "ug/L", down="Linear", MW = 0)
```

Arguments

fileName	file name to save
concData	concentration data table
colSubj	column name for subject ID
colTime	column name for time
colConc	column name for concentration
dose	administered dose
adm	one of "Bolus" or "Infusion" or "Extravascular" to indicate drug administration mode
dur	duration of infusion
doseUnit	unit of dose
timeUnit	unit of time
concUnit	unit of concentration
down	either of "Linear" or "Log" to indicate the way to calculate AUC and AUMC
MW	molecular weight of drug

Value

Basically same with [sNCA](#)

Author(s)

Kyun-Seop Bae <k@acr.kr>

See Also

[help](#), [sNCA](#), [txtNCA](#), [tabNCA](#), [rtfNCA](#)

Examples

```
pdfNCA(fileName="NCA-Theoph.pdf", Theoph, colSubj="Subject", colTime="Time",
        colConc="conc", dose=320, doseUnit="mg", timeUnit="h", concUnit="mg/L")
pdfNCA(fileName="NCA-Indometh.pdf", Indometh, colSubj="Subject", colTime="time",
        colConc="conc", adm="Infusion", dur=0.5, dose=25, doseUnit="mg",
        timeUnit="h", concUnit="mg/L")
```

Round	<i>Round Half Away from Zero</i>
-------	----------------------------------

Description

This is an ordinary rounding function, so called round half away from zero

Usage

```
Round(x, n = 0)
```

Arguments

x	numeric to be rounded
n	indicating decimal digits

Details

The function round in R base rounds to the even number, i.e. round(0.5) is 0 not 1. If you want rounding 0.5 be 1, you can use this Round function. This function is for the consistency with other software like MS-Excel, SAS.

Value

ordinarily rounded value

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

See wikipedia subject "Rounding"

Examples

```
(x = 1:10 - 0.5)
Round(x)
round(x) # compare with the above
```

RptCfg	<i>NCA Report Configuration Table</i>
--------	---------------------------------------

Description

Contains the names and order of column of return table/text by IndiNCA and NCA functions

Usage

```
RptCfg
```

Format

A data frame with 48 observations on the following 10 variables.

PPTTESTCD a character vector of CDISC SDTM PPTTESTCD

SYNONYM a character vector of CDISC SDTM PPTTESTCD Synonym

NCI a character vector of NCI preferred terms

WNL a character vector of WinNonlin(R) software variables

ExtravascularDefault a numeric vector of ordering in report for extravascular administration, Zero means exclusion in the report.

ExtravascularWNL a numeric vector of WinNonlin(R) style ordering in report for extravascular administration, Zero means exclusion in the report.

BolusDefault a numeric vector of ordering in report for extravascular administration, Zero means exclusion in the report.

BolusWNL a numeric vector of WinNonlin(R) style ordering in report for extravascular administration, Zero means exclusion in the report.

InfusionDefault a numeric vector of ordering in report for extravascular administration, Zero means exclusion in the report.

InfusionWNL a numeric vector of WinNonlin(R) style ordering in report for extravascular administration, Zero means exclusion in the report.

Details

This table should exist in NonCompart package. User can edit this table for shaping the report in one's own style.

rtfNCA	<i>NCA output to rtf file</i>
--------	-------------------------------

Description

This output NCA result in a rtf file.

Usage

```
rtfNCA(fileName = "Temp-NCA.rtf", concData, colSubj = "Subject", colTime = "Time",
        colConc = "conc", dose = 0, adm = "Extravascular", dur = 0, doseUnit = "mg",
        timeUnit = "h", concUnit = "ug/L", down="Linear", MW = 0)
```

Arguments

fileName	file name to save
concData	concentration data table
colSubj	column name for subject ID
colTime	column name for time
colConc	column name for concentration
dose	administered dose
adm	one of "Bolus" or "Infusion" or "Extravascular" to indicate drug administration mode
dur	duration of infusion
doseUnit	unit of dose
timeUnit	unit of time
concUnit	unit of concentration
down	either of "Linear" or "Log" to indicate the way to calculate AUC and AUMC
MW	molecular weight of drug

Value

Basically same with [sNCA](#)

Author(s)

Kyun-Seop Bae <k@acr.kr>

See Also

[help](#), [sNCA](#), [txtNCA](#), [tabNCA](#), [pdfNCA](#)

Examples

```
rtfNCA(fileName="NCA-Theoph.rtf", Theoph, colSubj="Subject", colTime="Time",
        colConc="conc", dose=320, doseUnit="mg", timeUnit="h", concUnit="mg/L")
rtfNCA(fileName="NCA-Indometh.rtf", Indometh, colSubj="Subject", colTime="time",
        colConc="conc", adm="Infusion", dur=0.5, dose=25, doseUnit="mg",
        timeUnit="h", concUnit="mg/L")
```

Slope*Get the Slope of regression $\log(y) \sim x$*

Description

It calculates the slope with linear regression of $\log(y) \sim x$

Usage

Slope(x, y)

Arguments

x	vector values of independent variable, usually time
y	vector values of dependent variable, usually concentration

Details

With time-concentration curve, you frequently need to estimate slope in $\log(\text{concentration}) \sim \text{time}$. This function is usually called by BestSlope function and you seldom need to call this function directly.

Value

R2	R-squared
R2ADJ	adjusted R-squared
LAMZNPT	number of points used for slope
LAMZ	negative of slope, λ_z
b0	intercept of regression line
CORRXY	correlation of $\log(y)$ and x
LAMZLL	earliest x for λ_z
LAMZUL	last x for λ_z
CLSTP	predicted y value at last point, predicted concentration for the last time point

Author(s)

Kyun-Seop Bae <k@acr.kr>

See Also

[BestSlope](#)

Examples

```
Slope(Indometh[Indometh$Subject==1, "time"], Indometh[Indometh$Subject==1, "conc"])
```

sNCA	<i>Simplest NCA</i>
------	---------------------

Description

This is the simplest function for NCA.

Usage

```
sNCA(x, y, dose = 0, adm = "Extravascular", dur = 0, doseUnit = "mg", timeUnit = "h",
      concUnit = "ug/L", iAUC = "", down = "Linear", MW = 0, returnNA = TRUE)
```

Arguments

x	usually time
y	usually concentration
dose	given amount
adm	one of "Bolus" or "Infusion" or "Extravascular" to indicate drug administration mode
dur	duration of infusion
doseUnit	unit of dose
timeUnit	unit of time
concUnit	unit of concentration
iAUC	interval AUCs to calculate
down	either of "Linear" or "Log" to indicate the way to calculate AUC and AUMC
MW	molecular weight of the drug
returnNA	if returnNA is TRUE, it returns NA values also.

Details

This will replace IndiNCA.

Value

C _{MAX}	maximum concentration, C _{max}
C _{MAXD}	dose normalized C _{max} , C _{MAX} / Dose, C _{max} / Dose
T _{MAX}	time of maximum concentration, T _{max}
T _{LAG}	time to observe the first non-zero concentration, for extravascular administration only
C _{LST}	last positive concentration observed, C _{last}
C _{LSTP}	last positive concentration predicted, C _{last_pred}
T _{LST}	time of last positive concentration, T _{last}
LAMZHL	half-life by lambda z, ln(2)/LAMZ
LAMZ	lambda_z negative of best fit terminal slope
LAMZLL	earliest time for LAMZ

LAMZUL	last time for LAMZ
LAMZNPT	number of points for LAMZ
CORRXY	correlation of log(concentration) and time
R2	R-squared
R2ADJ	R-squared adjusted
C0	back extrapolated concentration at time 0, for bolus intravascular administration only
AUCLST	AUC from 0 to TLST
AUCALL	AUC using all the given points, including trailing zero concentrations
AUCIFO	AUC infinity observed
AUCIFOD	AUCIFO / Dose
AUCIFP	AUC infinity predicted using CLSTP instead of CLST
AUCIFPD	AUCIFP / Dose
AUCPEO	AUC % extrapolation observed
AUCPEP	AUC % extrapolated for AUCIFP
AUCPBEO	AUC % back extrapolation observed, for bolus IV administration only
AUCPBEP	AUC % back extrapolation predicted with AUCIFP, for bolus IV administration only
AUMCLST	AUMC to the TLST
AUMCIFO	AUMC infinity observed using CLST
AUMCIFP	AUMC infinity determined by CLSTP
AUMCPEO	AUMC % extrapolated observed
AUMCPEP	AUMC % extrapolated predicted
MRTIVLST	mean residence time (MRT) to TLST, for intravascular administration
MRTIVIFO	mean residence time (MRT) infinity using CLST, for intravascular administration
MRTIVIFP	mean residence time (MRT) infinity using CLSTP, for intravascular administration
MRTEVLST	mean residence time (MRT) to TLST, for extravascular administration
MRTEVIFO	mean residence time (MRT) infinity using CLST, for extravascular administration
MRTEVIFP	mean residence time (MRT) infinity using CLSTP, for extravascular administration
VZO	volume of distribution determined by LAMZ and AUCIFO, for intravascular administration
VZP	volume of distribution determined by LAMZ and AUCIFP, for intravascular administration
VZF0	VZO for extravascular administration, VZO/F, F is bioavailability
VZFP	VZP for extravascular administration, VZP/F, F is bioavailability
CLO	clearance using AUCIFO, for intravascular administration
CLP	clearance using AUCIFP, for intravascular administration
CLF0	CLO for extravascular administration, CLO/F, F is bioavailability

CLFP	CLP for extravascular administration, CLP/F, F is bioavailability
VSS0	volume of distribution at steady state using CLST, for intravascular administration only
VSSP	volume of distribution at steady state using CLSTP, for intravascular administration only

Author(s)

Kyun-Seop Bae <k@acr.kr>

References

Gabrielsson J, Weiner D. Pharmacokinetic and Pharmacodynamic Data Analysis - Concepts and Applications. 5th ed. 2016.

See Also

[help](#), [tabNCA](#), [txtNCA](#), [pdfNCA](#), [rtfNCA](#)

Examples

```
# For one subject
x = Theoph[Theoph$Subject=="1", "Time"]
y = Theoph[Theoph$Subject=="1", "conc"]

sNCA(x, y, dose=320, doseUnit="mg", concUnit="mg/L", timeUnit="h")
sNCA(x, y, dose=320, concUnit="mg/L", returnNA=FALSE)

iAUC = data.frame(Name=c("AUC[0-12h]", "AUC[0-24h]"), Start=c(0,0), End=c(12,24))
sNCA(x, y, dose=320, doseUnit="mg", concUnit="mg/L", timeUnit="h", iAUC=iAUC)

MW = 180.164 # Molecular weight of theophylline

sNCA(x, y/MW, dose=320, doseUnit="mg", concUnit="mmol/L", timeUnit="h")
sNCA(x, y/MW, dose=320, doseUnit="mg", concUnit="mmol/L", timeUnit="h", MW=MW)
sNCA(x, y, dose=320/MW, doseUnit="mmol", concUnit="mg/L", timeUnit="h", MW=MW)
sNCA(x, y/MW, dose=320/MW, doseUnit="mmol", concUnit="mmol/L", timeUnit="h", MW=MW)

sNCA(x, y/MW, dose=320/MW, doseUnit="mmol", concUnit="mmol/L", timeUnit="h", MW=MW,
      returnNA=FALSE)
sNCA(x, y/MW, doseUnit="mmol", concUnit="mmol/L", timeUnit="h", MW=MW, returnNA=FALSE)
sNCA(x, y/MW, dose=as.numeric(NA), doseUnit="mmol", concUnit="mmol/L", timeUnit="h",
      MW=MW, returnNA=FALSE)

sNCA(x, y, dose=320, concUnit="mg/L", timeUnit="hr")
sNCA(x*60, y, dose=320, concUnit="mg/L", timeUnit="min")

# For all subjects
IDs = sort(unique(Theoph[, "Subject"]))
nID = length(IDs)
Res = vector()
for (i in 1:nID) {
  x = Theoph[Theoph[, "Subject"]==IDs[i], "Time"]
  y = Theoph[Theoph[, "Subject"]==IDs[i], "conc"]
  tRes = sNCA(x, y, dose=320, concUnit="mg/L", returnNA=FALSE)
  tRes = c(ID = IDs[i], tRes)
```



```

    Res = rbind(Res, tRes)
  }
  Res

```

tabNCA

Table output NCA

Description

This output NCA result to table form.

Usage

```

tabNCA(concData, colSubj = "Subject", colTime = "Time", colConc = "conc", dose = 0,
      adm = "Extravascular", dur = 0, doseUnit = "mg", timeUnit = "h",
      concUnit = "ug/L", down = "Linear", MW = 0, returnNA = FALSE)

```

Arguments

concData	concentration data table
colSubj	column name for subject ID
colTime	column name for time
colConc	column name for concentration
dose	administered dose
adm	one of "Bolus" or "Infusion" or "Extravascular" to indicate drug administration mode
dur	duration of infusion
doseUnit	unit of dose
timeUnit	unit of time
concUnit	unit of concentration
down	method to calculate AUC, "Linear" or "Log"
MW	molecular weight of drug
returnNA	if returnNA is TRUE, it returns NA values also.

Value

Basically same with [sNCA](#)

Author(s)

Kyun-Seop Bae <k@acr.kr>

See Also

[help](#), [sNCA](#), [txtNCA](#), [pdfNCA](#), [rtfNCA](#)

Examples

```

tabNCA(Theoph, dose=320, concUnit="mg/L")
tabNCA(Indometh, colSubj="Subject", colTime="time", colConc="conc", dose=25,
      adm="Infusion", dur=0.5, concUnit="mg/L")

```

txtNCA	<i>Text output of NCA</i>
--------	---------------------------

Description

This output NCA result in text form.

Usage

```
txtNCA(x, y, dose = 0, adm = "Extravascular", dur = 0, doseUnit = "mg", timeUnit = "h",
       concUnit = "ug/L", iAUC = "", down="Linear", MW = 0, returnNA = FALSE)
```

Arguments

x	usually time
y	usually concentration
dose	given amount
adm	one of "Bolus" or "Infusion" or "Extravascular" to indicate drug administration mode
dur	duration of infusion
doseUnit	unit of dose
timeUnit	unit of time
concUnit	unit of concentration
iAUC	interval AUCs to calculate
down	either of "Linear" or "Log" to indicate the way to calculate AUC and AUMC
MW	molecular weight of the drug
returnNA	if returnNA is TRUE, it returns NA values also.

Value

Basically same with [sNCA](#)

Author(s)

Kyun-Seop Bae <k@acr.kr>

See Also

[help](#), [sNCA](#), [tabNCA](#), [pdfNCA](#), [rtfNCA](#)

Examples

```
# For one subject
txtNCA(Theoph[Theoph$Subject=="1", "Time"], Theoph[Theoph$Subject=="1", "conc"],
       dose=320, doseUnit="mg", concUnit="mg/L", timeUnit="h")

# or equivalently
x = Theoph[Theoph$Subject=="1", "Time"]
y = Theoph[Theoph$Subject=="1", "conc"]
```

```

txtNCA(x, y, dose=320, doseUnit="mg", concUnit="mg/L", timeUnit="h")

# For all subjects
IDs = sort(as.numeric(unique(Theoph[, "Subject"])))
nID = length(IDs)
Res = vector()
for (i in 1:nID) {
  tRes = txtNCA(Theoph[Theoph[, "Subject"]==IDs[i], "Time"],
                Theoph[Theoph[, "Subject"]==IDs[i], "conc"],
                dose=320, concUnit="mg/L", returnNA=FALSE)
  tRes = c(paste("ID =", IDs[i]), tRes, "")
  Res = c(Res, tRes)
}
Res

```

Unit	<i>Display CDISC standard units and multiplied factor of NCA results</i>
------	--

Description

It displays CDISC PP output units and multiplication factor for them.

Usage

```
Unit(code = "", timeUnit = "h", concUnit = "ng/mL", doseUnit = "mg", MW = 0)
```

Arguments

code	vector of PPTESTCD
timeUnit	unit of time
concUnit	unit of concentration
doseUnit	unit of dose
MW	molecular weight of drug

Value

row names	PPTESTCD
Unit	unit
Factor	internal multiplication factor

Author(s)

Kyun-Seop Bae <k@acr.kr>

Examples

```
Unit(concUnit="ug/L", doseUnit="mg")
Unit(concUnit="ng/L", doseUnit="mg")

Unit(concUnit="umol/L", doseUnit="mmol")
Unit(concUnit="nmol/L", doseUnit="mmol")

Unit(concUnit="mmol/L", doseUnit="mg", MW=500)
Unit(concUnit="umol/L", doseUnit="mg", MW=500)
Unit(concUnit="nmol/L", doseUnit="mg", MW=500)
Unit(concUnit="nmol/mL", doseUnit="mg", MW=500)

Unit(concUnit="ug/L", doseUnit="mmol", MW=500)
Unit(concUnit="ug/L", doseUnit="mol", MW=500)
Unit(concUnit="ng/L", doseUnit="mmol", MW=500)
Unit(concUnit="ng/mL", doseUnit="mmol", MW=500)

Unit(concUnit="nmol/L", doseUnit="mg")
Unit(concUnit="ug/L", doseUnit="mmol")
```

Index

*Topic **AUC**

AUC, [3](#)

IntAUC, [5](#)

LinAUC, [7](#)

LogAUC, [8](#)

*Topic **NCA**

ncar-package, [2](#)

*Topic **Output Form**

pdfNCA, [9](#)

rtfNCA, [12](#)

sNCA, [14](#)

tabNCA, [17](#)

txtNCA, [18](#)

*Topic **Slope**

BestSlope, [4](#)

*Topic **datasets**

RptCfg, [11](#)

*Topic **interpolation**

Interpol, [6](#)

*Topic **interval AUC**

IntAUC, [5](#)

Interpol, [6](#)

*Topic **package**

ncar-package, [2](#)

*Topic **partial AUC**

IntAUC, [5](#)

Interpol, [6](#)

*Topic **rounding**

Round, [10](#)

*Topic **slope**

Slope, [13](#)

AUC, [3](#), [6](#), [8](#), [9](#)

BestSlope, [4](#), [13](#)

help, [10](#), [12](#), [16–18](#)

IntAUC, [5](#), [7](#)

Interpol, [6](#), [6](#)

LinAUC, [4](#), [7](#), [9](#)

LogAUC, [4](#), [8](#), [8](#)

ncar (ncar-package), [2](#)

ncar-package, [2](#)

pdfNCA, [9](#), [12](#), [16–18](#)

Round, [10](#)

RptCfg, [11](#)

rtfNCA, [10](#), [12](#), [16–18](#)

Slope, [5](#), [13](#)

sNCA, [10](#), [12](#), [14](#), [17](#), [18](#)

tabNCA, [10](#), [12](#), [16](#), [17](#), [18](#)

txtNCA, [10](#), [12](#), [16](#), [17](#), [18](#)

Unit, [19](#)