Package 'phonfieldwork'

July 23, 2025

Type Package

Title Linguistic Phonetic Fieldwork Tools

Version 0.0.17

Depends R (>= 3.5.0)

Imports tuneR, phonTools, grDevices, utils, graphics, rmarkdown, xml2, readr, tools, mime

Description There are a lot of different typical tasks that have to be solved during phonetic research and experiments. This includes creating a presentation that will contain all stimuli, renaming and concatenating multiple sound files recorded during a session, automatic annotation in 'Praat' TextGrids (this is one of the sound annotation standards provided by 'Praat' software, see Boersma & Weenink 2020 <https://www.fon.hum.uva.nl/praat/>), creating an html table with annotations and spectrograms, and converting multiple formats ('Praat' TextGrid, 'ELAN', 'EXMARaLDA', 'Audacity', subtitles '.srt', and 'FLEx' flextext). All of these tasks can be solved by a mixture of different tools (any programming language has programs for automatic renaming, and Praat contains scripts for concatenating and renaming files, etc.). 'phonfieldwork' provides a functionality that will make it easier to solve those tasks independently of any additional tools. You can also compare the functionality with other packages: 'rPraat' <https://CRAN.R-project.org/package=rPraat>, 'textgRid' <https://CRAN.R-project.org/package=textgRid>.

License GPL (>= 2)

SystemRequirements pandoc (>= 1.14) - http://pandoc.org

URL https://CRAN.R-project.org/package=phonfieldwork, https://docs.ropensci.org/phonfieldwork/

BugReports https://github.com/ropensci/phonfieldwork/issues

Encoding UTF-8

RoxygenNote 7.3.2

VignetteBuilder knitr

Suggests knitr, tidyr, dplyr, DT, lingtypology, testthat, readxl

Language en-US

NeedsCompilation no

Author George Moroz [aut, cre] (ORCID:
<https://orcid.org/0000-0003-1990-6083>),
Jonathan Keane [rev] (ORCID: <https://orcid.org/0000-0001-7087-9776>),
Niko Partanen [rev] (ORCID: <https://orcid.org/0000-0001-8584-3880>),
Valeria Buntiakova [ctb] (ORCID:
<https://orcid.org/0000-0003-2409-2651>)

Maintainer George Moroz <agricolamz@gmail.com>

Repository CRAN

Date/Publication 2024-07-29 17:40:02 UTC

Contents

add_leading_symbols . . . 3
annotate_textgrid . . . 3
audacity_to_df . . . 4
concatenate_soundfiles . . . 5
concatenate_textgrids . . . 6
create_empty_textgrid . . . 7
create_glossed_document . . . 8
create_image_look_up . . . 9
create_presentation . . . 10
create_sound_play . . . 11
create_subannotation . . . 12
create_viewer . . . 13
df_to_eaf . . . 14
df_to_exb . . . 15
df_to_tier . . . 16
draw_sound . . . 17
draw_spectrogram . . . 20
eaf_to_df . . . 22
exb_to_df . . . 23
extract_intervals . . . 24
flextext_to_df . . . 25
formant_to_df . . . 25
get_sound_duration . . . 26
get_textgrid_names . . . 27
intensity_to_df . . . 27
pitch_to_df . . . 28
read_from_folder . . . 29
remove_textgrid_tier . . . 29
rename_soundfiles . . . 30
set_textgrid_names . . . 31
srt_to_df . . . 32
textgrid_to_df . . . 32
tier_to_df . . . 33

Index **34**

`add_leading_symbols` *Create indices padded with zeros*

Description

Create indices padded with zeros. This is important for creating appropriate for sorting names.

Usage

```
add_leading_symbols(file_names)
```

Arguments

`file_names`	vector of any values.

Value

A string with numbers padded with leadinng zero.

Author(s)

George Moroz <agricolamz@gmail.com>

`annotate_textgrid` *Annotate textgrid*

Description

Annotates textgrids. It is possible to define step in the argument "each", so each second element of the tier will be annotated.

Usage

```
annotate_textgrid(
  annotation,
  textgrid,
  tier = 1,
  each = 1,
  backup = TRUE,
  write = TRUE
)
```

Arguments

annotation	vector of stimuli
textgrid	character with a filename or path to the TextGrid
tier	value that could be either ordinal number of the tier either name of the tier
each	non-negative integer. Each element of x is repeated each times
backup	logical. If TRUE (by default) it creates a backup tier.
write	logical. If TRUE (by dafault) it overwrites an existing tier.

Value

a string that contain TextGrid. If argument write is TRUE, then no output.

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
annotate_textgrid(
  annotation = c("", "t", "e", "s", "t"),
  textgrid = system.file("extdata",
    "test.TextGrid",
    package = "phonfieldwork"
  ),
  tier = 2, write = FALSE
)
```

---

audacity_to_df *Audacity's labels to dataframe*

Description

Audacity make it possible to annotate sound files with labels that can be exported as a .tsv file with .txt extension. This function convert result to dataframe.

Usage

```
audacity_to_df(file_name)
```

Arguments

file_name	file_name string with a filename or path to the .txt file produced by Audacity

Value

a dataframe with columns: content, time_start, time_end, source.

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
audacity_to_df(system.file("extdata",
  "test_audacity.txt",
  package = "phonfieldwork"
))
```

`concatenate_soundfiles` *Concatenate sounds*

Description

Creates a merged sound file from old sound files in a folder. If the annotation argument is not equal to `NULL`, it creates an annotation file (Praat .TextGrid, ELAN .eaf or EXMARaLDA .exb) with original sound names annotation.

Usage

```
concatenate_soundfiles(
  path,
  result_file_name = "concatenated",
  annotation = "textgrid",
  separate_duration = 0
)
```

Arguments

`path`	path to the directory with soundfiles.
`result_file_name`	name of the result and annotation files.
`annotation`	character. There are several variants: "textgrid" for Praat TextGrid, "eaf" for ELAN's .eaf file, or "exb" for EXMARaLDA's .exb file. It is also possible to use `NULL` in order to prevent the creation of the annotation file.
`separate_duration`	double. It is possible to add some silence between concatenated sounds. This variable denotes duration of this soundless separator in seconds.

Value

no output

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
# create two files in a temprary folder "test_folder"
s1 <- system.file("extdata", "test.wav", package = "phonfieldwork")
s2 <- system.file("extdata", "post.wav", package = "phonfieldwork")
tdir <- tempdir()
file.copy(c(s1, s2), tdir)

# here are two .wav files in a folder
list.files(tdir)
# [1] "post.wav" "test.wav" ...

# Concatenate all files from the folder into concatenated.wav and create
# corresponding TextGrid
concatenate_soundfiles(path = tdir, result_file_name = "concatenated")

list.files(tdir)
# [1] "concatenated.TextGrid" "concatenated.wav" "post.wav" "test.wav" ...
```

---

concatenate_textgrids *Concatenate TextGrids*

Description

Creates a merged TextGrids from TextGrids files in a folder.

Usage

```
concatenate_textgrids(path, result_file_name = "concatenated")
```

Arguments

`path`	path to the directory with soundfiles.
`result_file_name`	name of the result and annotation files.

Value

no output

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
# create two files in a temprary folder "test_folder"
t1 <- system.file("extdata", "test.TextGrid", package = "phonfieldwork")
t2 <- system.file("extdata", "post.TextGrid", package = "phonfieldwork")
tdir <- tempdir()
file.copy(c(t1, t2), tdir)

# here are two .wav files in a folder
list.files(tdir)
# [1] "post.TextGrid" "test.TextGrid" ...

# Concatenate all TextGrids from the folder into concatenated.TextGrid
concatenate_textgrids(path = tdir, result_file_name = "concatenated")

list.files(tdir)
# [1] "concatenated.TextGrid" "post.TextGrid" "test.TextGrid" ...
```

---

create_empty_textgrid *Create an empty TextGrid*

Description

Creates an empty Praat TextGrid in the same folder as a reference sound file. It is possible to manage with predefined number of tiers, their names and their types.

Usage

```
create_empty_textgrid(
  duration,
  tier_name = NULL,
  point_tier = NULL,
  path,
  result_file_name = "new_textgrid"
)
```

Arguments

duration	integer. Duration of the textgrid. If you do not know the duration of your audio file use the `get_sound_duration()` function.
tier_name	a vector that contain tier names.
point_tier	a vector that defines which tiers should be made point tiers. This argument excepts numeric values (e. g. `c(2, 4)` means second and forth tiers) or character (e. g. `c("a", "b")` means tiers with names "a" and "b")
path	path to the directory with soundfiles.
result_file_name	name of the result and annotation files.

Value

The function returns no output, just creates a Praat TextGrid in the same folder as a reference sound file.

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
tmp <- tempfile(fileext = ".TextGrid")
create_empty_textgrid(1, path = dirname(tmp), result_file_name = basename(tmp))
```

---

create_glossed_document

Create a glossed document

Description

Creates a file with glossed example (export from .flextext or other formats)

Usage

```
create_glossed_document(
  flextext = NULL,
  rows = c("gls"),
  output_dir,
  output_file = "glossed_document",
  output_format = "html",
  example_pkg = NULL
)
```

Arguments

flextext	path to a .flextext file or a dataframe with the following columns: p_id, s_id, w_id, txt, cf, hn, gls, msa, morph, word, phrase, paragraph, free_trans, text, text_title
rows	vector of row names from the flextext that should appear in the final document. Possible values are: "cf", "hn", "gls", "msa". "gls" is default.
output_dir	the output directory for the rendered file
output_file	the name of the result .html file (by default glossed_document).
output_format	The option can be "html" or "docx"
example_pkg	vector with name of the LaTeX package for glossing (possible values: "gb4e", "langsci", "expex", "philex")

Value

If `render` is `FALSE`, the function returns a path to the temporary file with .csv file. If `render` is `TRUE`, there is no output in a function.

Author(s)

George Moroz <agricolamz@gmail.com>

`create_image_look_up` *Create image look_up objects for html viewer*

Description

Create image look_up objects for html viewer

Usage

```
create_image_look_up(img_src, img_caption = NULL, text = "&#x1f441;")
```

Arguments

`img_src`	string or vector of strings with a image(s) path(s).
`img_caption`	string or vector of strings that will be displayed when image is clicked.
`text`	string o vector of strings that will be displayed as view link. By default it is eye emoji (👁).

Value

a string or vector of strings

Author(s)

George Moroz <agricolamz@gmail.com>

`create_presentation` *Creates a presentation*

Description

Creates an html or powerpoint presentation in a working directory from list of words and translations. Here is an example of such presentation.

Usage

```
create_presentation(
  stimuli,
  translations = "",
  external = NULL,
  font_size = 50,
  output_dir,
  output_format = "html",
  output_file = "stimuli_presentation",
  render = TRUE
)
```

Arguments

`stimuli`	the vector of stimuli (obligatory). Can be a path to an image.
`translations`	the vector of translations (optional)
`external`	the vector with the indices of external images
`font_size`	font size in px (50, by default)
`output_dir`	the output directory for the rendered file
`output_format`	the string that difine the R Markdown output format: "html" (by default) or "pptx"
`output_file`	the name of the result presentation file (by default stimuli_presentation)
`render`	the logical argument, if `TRUE` render the created R Markdown presentation to the `output_dir` folder, otherwise returns the path to the temporary file with a Rmd file.

Value

If `render` is `FALSE`, the function returns a path to the temporary file. If `render` is `TRUE`, there is no output in a function.

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
create_presentation(
  stimuli = c("rzeka", "drzewo"),
  translations = c("river", "tree"),
  render = FALSE
)

# with image
create_presentation(
  stimuli = c(
    "rzeka", "drzewo",
    system.file("extdata", "r-logo.png",
      package = "phonfieldwork"
    )
  ),
  translations = c("river", "tree", ""),
  external = 3,
  render = FALSE
)
```

`create_sound_play` *Create audio play objects for html viewer*

Description

Create audio play objects for html viewer

Usage

```
create_sound_play(snd_src, text = "&#x1f442;")
```

Arguments

`snd_src`	string or vector of strings with a image(s) path(s).
`text`	string o vector of strings that will be displayed as view link. By default it is ear emoji (👂).

Value

a string or vector of strings

Author(s)

George Moroz <agricolamz@gmail.com>

`create_subannotation` *Create boundaries in a texgrid tier*

Description

Create boundaries in a texgrid tier

Usage

```
create_subannotation(
  textgrid,
  tier = 1,
  new_tier_name = "",
  n_of_annotations = 4,
  each = 1,
  omit_blank = TRUE,
  overwrite = TRUE
)
```

Arguments

`textgrid`	character with a filename or path to the TextGrid
`tier`	value that could be either ordinal number of the tier either name of the tier
`new_tier_name`	a name of a new created tier
`n_of_annotations`	number of new annotations per annotation to create
`each`	non-negative integer. Each new blank annotation is repeated every first, second or ... times
`omit_blank`	logical. If TRUE (by dafault) it doesn't create subannotation for empy annotations.
`overwrite`	logical. If TRUE (by dafault) it overwrites an existing tier.

Value

a string that contain TextGrid. If argument write is `TRUE`, then no output.

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
create_subannotation(system.file("extdata", "test.TextGrid",
  package = "phonfieldwork"
),
tier = 1, overwrite = FALSE
)
```

`create_viewer` *Create an annotation viewer*

Description

Creates an html file with table and sound preview and player

Usage

```
create_viewer(
  audio_dir,
  picture_dir = NULL,
  table,
  captions = NULL,
  sorting_columns = NULL,
  about = "Created with the `phonfieldworks` package (Moroz 2020).",
  map = FALSE,
  output_dir,
  output_file = "stimuli_viewer",
  render = TRUE
)
```

Arguments

`audio_dir`	path to the directory with sounds
`picture_dir`	path to the directory with pictures
`table`	data frame with data ordered according to files in the audio folder
`captions`	vector of strings that will be used for captions for a picture.
`sorting_columns`	vector of strings for sorting the result column
`about`	it is either .Rmd file or string with the text for about information: author, project, place of gahtered information and other metadata, version of the viewer and so on
`map`	the logical argument, if `TRUE` and there is a `glottocode` column in `table`
`output_dir`	the output directory for the rendered file
`output_file`	the name of the result .html file (by default stimuli_viewer)
`render`	the logical argument, if `TRUE` renders the created R Markdown viewer to the `output_dir` folder, otherwise returns the path to the temporary file with a .csv file.

Value

If `render` is `FALSE`, the function returns a path to the temporary file with .csv file. If `render` is `TRUE`, there is no output in a function.

Author(s)

George Moroz <agricolamz@gmail.com>

`df_to_eaf` *Dataframe to .eaf*

Description

Convert a dataframe to Elan file .exb

Usage

```
df_to_eaf(df, output_file, output_dir = "", ref_file = "", mime_type = "")
```

Arguments

`df`	an R dataframe object that contains columns named 'tier', 'id', 'tier_name', 'content', 'time_start', 'time_end' and preferably also 'tier_type', 'stereotype', 'tier_ref', 'event_local_id', 'dependent_on' that are specific for eaf file
`output_file`	the name of the result .xml file
`output_dir`	the output directory for the rendered file (defalut is used if not spectified)
`ref_file`	a filepath for connected media file (not obligatory)
`mime_type`	a MIME type of connected media file (not obligatory)

Value

.xml file

Author(s)

Sergej Kudrjashov <xenomirant@gmail.com>

Examples

```
df <- eaf_to_df(system.file("extdata", "test.eaf", package = "phonfieldwork"))

df_to_eaf(df = df,
          output_file = 'test.eaf',
          ref_file = 'test.wav')

# Remove file in order to pass checks

file.remove("test.eaf")
```

df_to_exb *Dataframe to EXMARaLDA's .exb*

Description

Convert a dataframe to EXMARaLDA's .exb

Usage

```
df_to_exb(
  df,
  name,
  output_file,
  output_dir = "",
  referenced_file = "",
  ud_meta = NULL,
  speaker_table = NULL
)
```

Arguments

df	an R dataframe object that contains columns named 'tier', 'tier_name', 'content', 'time_start', 'time_end' and 'id'
name	transcription name
output_file	the name of the result .html file
output_dir	the output directory for the rendered file
referenced_file	a filepath for .wav
ud_meta	a vector ('key':'value') of meta information (not obligatory)
speaker_table	a table with speaker information; must include columns 'id', 'abbreviation', 'sex' (not obligatory)

Value

.xml file

Author(s)

Valeria Buntiakova <valleriabun@gmail.com>

Examples

```
meta <- c('Type of communication' = 'Fernsehinterview',
          'Source' = 'Parkinson Talkshow auf BBC',
          'Background information' = 'Interview mit den Beckhams',
          'Code' = 'Beckhams')
```

```
speaker_data <- data.frame('id' = c('SPK0', 'SPK1', 'SPK2'),
                           'abbreviation' = c('PAR', 'VIC', 'DAV'),
                           'sex' = c('m', 'f', 'm'),
                           'Family: Marital status' = c('Verheiratet',
                                                        'Verheiratet',
                                                        'Verheiratet'),
                           'Birth' = c('28. März 1935 in Cudworth',
                                       '14. April 1974 in Hertfordshire',
                                       '2. Mail 1975 in London'),
                           'Occupation' = c('Fernsehmoderator, Journalist, Autor',
                                            'Sängerin',
                                            'Professioneller Fußballspieler'),
                     'Family: Children' = c(3, '3 Söhn, 1 Tochter', '3 Söhne, 1 Tochter'),
                    'Name' = c('Michael Parkinson', 'Victoria Beckham', 'David Beckham'))

df <- exb_to_df(system.file("extdata", "demo_Beckhams.exb", package = "phonfieldwork"))

df_to_exb(df = df,
          name = 'Beckhams',
          output_file = 'beck.xml',
          referenced_file = 'beck.wav',
          ud_meta = meta,
          speaker_table = speaker_data)

# Remove file in order to pass checks

file.remove("beck.xml")
```

`df_to_tier` *Dataframe to TextGrid's tier*

Description

Convert a dataframe to a Praat TextGrid.

Usage

```
df_to_tier(df, textgrid, tier_name = "", overwrite = TRUE)
```

Arguments

`df`	an R dataframe object that contains columns named "content", "time_start" and "time_end"
`textgrid`	a character with a filename or path to the TextGrid
`tier_name`	a vector that contain a name for a created tier
`overwrite`	a logic argument, if `TRUE` overwrites the existing TextGrid file

Value

If `overwrite` is `FALSE`, then the function returns a vector of strings with a TextGrid. If `overwrite` is `TRUE`, then no output.

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
time_start <- c(0.00000000, 0.01246583, 0.24781914, 0.39552363, 0.51157715)
time_end <- c(0.01246583, 0.24781914, 0.39552363, 0.51157715, 0.65267574)
content <- c("", "T", "E", "S", "T")
df_to_tier(data.frame(id = 1:5, time_start, time_end, content),
  system.file("extdata", "test.TextGrid",
    package = "phonfieldwork"
  ),
  overwrite = FALSE
)
```

`draw_sound` *Draw Oscilogram, Spectrogram and annotation*

Description

Create oscilogram and spectrogram plot.

Usage

```
draw_sound(
  file_name,
  annotation = NULL,
  from = NULL,
  to = NULL,
  zoom = NULL,
  text_size = 1,
  output_file = NULL,
  title = NULL,
  freq_scale = "kHz",
  frequency_range = c(0, 5),
  dynamic_range = 50,
  window_length = 5,
  window = "kaiser",
  windowparameter = -1,
  preemphasisf = 50,
  spectrum_info = TRUE,
  raven_annotation = NULL,
  formant_df = NULL,
```

```
  pitch = NULL,
  pitch_range = c(75, 350),
  intensity = NULL,
  output_width = 750,
  output_height = 500,
  output_units = "px",
  sounds_from_folder = NULL,
  textgrids_from_folder = NULL,
  pic_folder_name = "pics",
  title_as_filename = TRUE,
  prefix = NULL,
  suffix = NULL,
  autonumber = FALSE
)
```

Arguments

file_name	a sound file
annotation	a source for annotation files (path to TextGrid file or dataframe created from other linguistic types, e. g. via `textgrid_to_df()`, `eaf_to_df()` or other functions)
from	Time in seconds at which to start extraction.
to	Time in seconds at which to stop extraction.
zoom	numeric vector of zoom window time (in seconds). It will draw the whole oscilogram and part of the spectrogram.
text_size	numeric, text size (default = 1).
output_file	the name of the output file
title	the title for the plot
freq_scale	a string indicating the type of frequency scale. Supported types are: "Hz" and "kHz".
frequency_range	vector with the range of frequencies to be displayed for the spectrogram up to a maximum of fs/2. By default this is set to 0-5 kHz.
dynamic_range	values greater than this many dB below the maximum will be displayed in the same color
window_length	the desired analysis window length in milliseconds.
window	A string indicating the type of window desired. Supported types are: "rectangular", "hann", "hamming", "cosine", "bartlett", "gaussian", and "kaiser".
windowparameter	The parameter necessary to generate the window, if appropriate. At the moment, the only windows that require parameters are the Kaiser and Gaussian windows. By default, these are set to 2 for kaiser and 0.4 for gaussian windows.
preemphasisf	Preemphasis of 6 dB per octave is added to frequencies above the specified frequency. For no preemphasis, set to a frequency higher than the sampling frequency.

`spectrum_info` logical. If `TRUE` then add information about window method and params.

`raven_annotation`
: Raven (Center for Conservation Bioacoustics) style annotations (boxes over spectrogram). The dataframe that contains `time_start`, `time_end`, `freq_low` and `freq_high` columns. Optional columns are `colors` and `content`.

`formant_df` dataframe with formants from `formant_to_df()` function

`pitch` path to the Praat '.Pitch' file or result of `pitch_to_df()` function. This variable provide data for visualisation of a pitch contour exported from Praat.

`pitch_range` vector with the range of frequencies to be displayed. By default this is set to 75-350 Hz.

`intensity` path to the Praat '.Intensity' file or result of `intensity_to_df()` function. This variable provide data for visualisation of an intensity contour exported from Praat.

`output_width` the width of the device

`output_height` the height of the device

`output_units` the units in which height and width are given. Can be "px" (pixels, the default), "in" (inches), "cm" or "mm".

`sounds_from_folder`
: path to a folder with multiple sound files. If this argument is not `NULL`, then the function goes through all files and creates picture for all of them.

`textgrids_from_folder`
: path to a folder with multiple .TextGrid files. If this argument is not `NULL`, then the function goes through all files and create picture for all of them.

`pic_folder_name`
: name for a folder, where all pictures will be stored in case `sounds_from_folder` argument is not `NULL`

`title_as_filename`
: logical. If true adds filename title to each picture

`prefix` prefix for all file names for created pictures in case `sounds_from_folder` argument is not `NULL`

`suffix` suffix for all file names for created pictures in case `sounds_from_folder` argument is not `NULL`

`autonumber` if TRUE automatically add number of extracted sound to the file_name. Prevents from creating a duplicated files and wrong sorting.

Value

Oscilogram and spectrogram plot (and possibly TextGrid annotation).

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
draw_sound(system.file("extdata", "test.wav", package = "phonfieldwork"))

draw_sound(
  system.file("extdata", "test.wav", package = "phonfieldwork"),
  system.file("extdata", "test.TextGrid",
    package = "phonfieldwork"
  )
)

draw_sound(system.file("extdata", "test.wav", package = "phonfieldwork"),
  system.file("extdata", "test.TextGrid", package = "phonfieldwork"),
  pitch = system.file("extdata", "test.Pitch",
    package = "phonfieldwork"
  ),
  pitch_range = c(50, 200)
)
draw_sound(system.file("extdata", "test.wav", package = "phonfieldwork"),
  system.file("extdata", "test.TextGrid", package = "phonfieldwork"),
  pitch = system.file("extdata", "test.Pitch",
    package = "phonfieldwork"
  ),
  pitch_range = c(50, 200),
  intensity = intensity_to_df(system.file("extdata", "test.Intensity",
    package = "phonfieldwork"
  ))
)
draw_sound(system.file("extdata", "test.wav", package = "phonfieldwork"),
  formant_df = formant_to_df(system.file("extdata", "e.Formant",
    package = "phonfieldwork"
  ))
)
```

---

draw_spectrogram *Draw spectrograms*

Description

This function was slightly changed from `phonTools::spectrogram()`. Argument description is copied from `phonTools::spectrogram()`.

Usage

```
draw_spectrogram(
  sound,
  fs = 22050,
  text_size = 1,
  window_length = 5,
```

```
  dynamic_range = 50,
  window = "kaiser",
  windowparameter = -1,
  freq_scale = "kHz",
  spectrum_info = TRUE,
  timestep = -1000,
  padding = 10,
  preemphasisf = 50,
  frequency_range = c(0, 5),
  nlevels = dynamic_range,
  x_axis = TRUE,
  title = NULL,
  raven_annotation = NULL,
  formant_df = NULL
)
```

Arguments

sound	Either a numeric vector representing a sequence of samples taken from a sound wave or a sound object created with the loadsound() or makesound() functions.
fs	The sampling frequency in Hz. If a sound object is passed this does not need to be specified.
text_size	numeric, text size (default = 1).
window_length	The desired analysis window length in milliseconds.
dynamic_range	Values greater than this many dB below the maximum will be displayed in the same color.
window	A string indicating the type of window desired. Supported types are: rectangular, hann, hamming, cosine, bartlett, gaussian, and kaiser.
windowparameter	The parameter necessary to generate the window, if appropriate. At the moment, the only windows that require parameters are the Kaiser and Gaussian windows. By default, these are set to 2 for kaiser and 0.4 for gaussian windows.
freq_scale	a string indicating the type of frequency scale. Supported types are: "Hz" and "kHz".
spectrum_info	logical. If TRUE then add information about window method and params.
timestep	If a negative value is given, -N, then N equally-spaced time steps are calculated. If a positive number is given, this is the spacing between adjacent analyses, in milliseconds.
padding	The amount of zero padding for each window, measured in units of window length. For example, if the window is 50 points, and padding = 10, 500 zeros will be appended to each window.
preemphasisf	Preemphasis of 6 dB per octave is added to frequencies above the specified frequency. For no preemphasis, set to a frequency higher than the sampling frequency.

frequency_range
: vector with the range of frequencies to be displayed for the spectrogram up to a maximum of fs/2. This is set to 0-5 kHz by default.

nlevels
: The number of divisions to be used for the z-axis of the spectrogram. By default it is set equal to the dynamic range, meaning that a single color represents 1 dB on the z-axis.

x_axis
: If TRUE then draw x axis.

title
: Character with the title.

raven_annotation
: Raven (Center for Conservation Bioacoustics) style annotations (boxes over spectrogram). The dataframe that contains time_start, time_end, freq_low and freq_high columns. Optional columns are colors and content.

formant_df
: dataframe with formants from formant_to_df() function

Value

Plot the comptued spectrogram

Author(s)

Santiago Barreda <sbarreda@ucdavis.edu>

Examples

```
draw_spectrogram(system.file("extdata", "test.wav",
  package = "phonfieldwork"
))
```

---

eaf_to_df *ELAN's .eaf file to dataframe*

Description

Convert .eaf file from ELAN to a dataframe.

Usage

```
eaf_to_df(file_name)
```

Arguments

file_name
: string with a filename or path to the .eaf file

Value

a dataframe with columns: `tier`, `id`, `content`, `tier_name`, `tier_type`, `tier_ref`, `event_local_id`, `dependent_on`, `time_start`, `time_end`, `source`, `media_url` and attributes: `MEDIA_URL`, `MIME_TYPE`, `RELATIVE_MEDIA_URL`.

Author(s)

George Moroz <agricolamz@gmail.com>

Kudrjashov Sergej <xenomirant@gmail.com>

Examples

```
eaf_to_df(system.file("extdata", "test.eaf", package = "phonfieldwork"))
```

`exb_to_df` *EXMARaLDA's .exb file to dataframe*

Description

Convert .exb file from EXMARaLDA to a dataframe.

Usage

```
exb_to_df(file_name)
```

Arguments

`file_name`	string with a filename or path to the .exb file

Value

a dataframe with columns: `tier`, `id`, `content`, `tier_name`, `tier_type`, `tier_category`, `tier_speaker`, `time_start`, `time_end`, `source`.

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
exb_to_df(system.file("extdata", "test.exb", package = "phonfieldwork"))
```

`extract_intervals` *Extract intervals*

Description

Extract sound according to non-empty annotated intervals from TextGrid and create soundfiles with correspondent names.

Usage

```
extract_intervals(
  file_name,
  textgrid,
  tier = 1,
  prefix = NULL,
  suffix = NULL,
  autonumber = TRUE,
  path
)
```

Arguments

`file_name`	path to the soundfile
`textgrid`	path to the TextGrid
`tier`	tier number or name that should be used as base for extraction and names
`prefix`	character vector containing prefix(es) for file names
`suffix`	character vector containing suffix(es) for file names
`autonumber`	if TRUE automatically add number of extracted sound to the file_name. Prevents from creating a duplicated files and wrong sorting.
`path`	path to the directory where create extracted soundfiles.

Value

no output

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
# create two files in a temprary folder "test_folder"
s <- system.file("extdata", "test.wav", package = "phonfieldwork")
tdir <- tempdir()
file.copy(s, tdir)
```

```
# Extract intervals according the TextGrid into the path
extract_intervals(
  file_name = paste0(tdir, "/test.wav"),
  textgrid = system.file("extdata", "test.TextGrid",
    package = "phonfieldwork"
  ),
  path = tdir
)

list.files(tdir)
# [1] "e-2.wav" "s-3.wav" "t-1.wav" "t-4.wav" "test.wav"
```

`flextext_to_df` *FLEX's .flextext file to dataframe*

Description

Convert .flextext file from FLEX to a dataframe.

Usage

```
flextext_to_df(file_name)
```

Arguments

`file_name`	string with a filename or path to the .flextext file

Value

a dataframe with columns: `p_id`, `s_id`, `w_id`, `txt`, `cf`, `hn`, `gls`, `msa`, `morph`, `word`, `phrase`, `paragraph`, `free_trans`, `text`, `text_title`

Author(s)

George Moroz <agricolamz@gmail.com>

`formant_to_df` *Praat Formant object to dataframe*

Description

Convert a Praat Formant object to a dataframe.

Usage

```
formant_to_df(file_name)
```

Arguments

file_name	string with a filename or path to the Formant file

Value

a dataframe with columns: time_start, time_end, frequency, bandwidth and formant

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
formant_to_df(system.file("extdata", "e.Formant", package = "phonfieldwork"))
```

---

get_sound_duration *Get file(s) duration*

Description

Calculate sound(s) duration.

Usage

```
get_sound_duration(file_name)
```

Arguments

file_name	a sound file

Value

Dataframe with two columns: file name and duration

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
get_sound_duration(
  system.file("extdata", "test.wav", package = "phonfieldwork")
)
```

get_textgrid_names *Extract TextGrid names*

Description

Extract TextGrid names.

Usage

```
get_textgrid_names(textgrid)
```

Arguments

textgrid	path to the TextGrid

Value

return a vector of tier names from given TextGrid

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
get_textgrid_names(system.file("extdata", "test.TextGrid",
  package = "phonfieldwork"
))
```

intensity_to_df *Praat Intensity tier to dataframe*

Description

Convert a Praat Intensity tier to a dataframe.

Usage

```
intensity_to_df(file_name)
```

Arguments

file_name	string with a filename or path to the Intensity tier

Value

a dataframe with columns: time_start, time_end, Intensity

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
intensity_to_df(system.file("extdata", "test.Intensity", package = "phonfieldwork"))
```

---

pitch_to_df *Praat Pitch tier to dataframe*

Description

Convert a Praat Pitch tier to a dataframe.

Usage

```
pitch_to_df(file_name, candidates = "")
```

Arguments

file_name	string with a filename or path to the Pitch tier
candidates	Praat Pitch tier contains multiple candidates for each time slice, use the value "all" if you want to get them all

Value

a dataframe with columns: time_start, time_end, frequency and, if candidates = "all", candidate_id and strength

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
pitch_to_df(system.file("extdata", "test.Pitch", package = "phonfieldwork"))
```

read_from_folder *Read multiple files from the folder*

Description

This function reads multiple files from the folder. The first argument is the path, the second argument is the type of files to read.

Usage

```
read_from_folder(path, type = "textgrid")
```

Arguments

path	to a folder with multiple sound files.
type	should be one of the following: "duration", "audacity", "eaf", "exb", "flextext", "formant", "intensity", "picth", "srt", "textgrid"

Value

dataframe with contents of all files of a selected type

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
read_from_folder(system.file("extdata", package = "phonfieldwork"), "eaf")
```

remove_textgrid_tier *Remove tier from texgrid*

Description

Remove tier from texgrid

Usage

```
remove_textgrid_tier(textgrid, tier, overwrite = TRUE)
```

Arguments

textgrid	character with a filename or path to the TextGrid
tier	value that could be either ordinal number of the tier either name of the tier
overwrite	logical. If TRUE (by dafault) it overwrites an existing tier.

Value

a string that contain TextGrid. If argument write is TRUE, then no output.

`rename_soundfiles` *Rename soundfiles*

Description

Rename soundfiles using the template from user.

Usage

```
rename_soundfiles(
  stimuli,
  translations = NULL,
  prefix = NULL,
  suffix = NULL,
  order = NULL,
  missing = NULL,
  path,
  autonumbering = TRUE,
  backup = TRUE,
  logging = TRUE
)
```

Arguments

`stimuli`	character vector of stimuli
`translations`	character vector of translations (optonal). This values are added after stimuli to the new files' names so the result will be `...stimulus_translation...`.
`prefix`	character vector of length one containing prefix for file names
`suffix`	character vector of length one containing suffix for file names
`order`	numeric vector that define the order of stimuli. By default the order of the stimuli is taken.
`missing`	numeric vector that define missing stimuli in case when some stimuli are not recorded.
`path`	path to the directory with soundfiles.
`autonumbering`	logical. If TRUE, function creates an automatic numbering of files.
`backup`	logical. If TRUE, function creates backup folder with all files. By default is TRUE.
`logging`	logical. If TRUE creates a .csv file with the correspondences of old names and new names. This could be useful for restoring in case something goes wrong.

Value

no output

Author(s)

George Moroz <agricolamz@gmail.com>

`set_textgrid_names` *Rewrite TextGrid names*

Description

Rewrite TextGrid names.

Usage

```
set_textgrid_names(textgrid, tiers, names, write = TRUE)
```

Arguments

`textgrid`	path to the TextGrid
`tiers`	integer vector with the number of tiers that should be named
`names`	vector of strings with new names for TextGrid tiers
`write`	logical. If TRUE (by dafault) it overwrites an existing tier

Value

a string that contain TextGrid. If argument write is `TRUE`, then no output.

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
set_textgrid_names(system.file("extdata", "test.TextGrid",
  package = "phonfieldwork"
),
tiers = 3, names = "new_name", write = FALSE
)
```

srt_to_df *Subtitles .srt file to dataframe*

Description

Convert subtitles .srt file to a dataframe.

Usage

```
srt_to_df(file_name)
```

Arguments

file_name	string with a filename or path to the .srt file

Value

a dataframe with columns: id, content, time_start, time_end, source.

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
srt_to_df(system.file("extdata", "test.srt", package = "phonfieldwork"))
```

textgrid_to_df *TextGrid to dataframe*

Description

Convert Praat TextGrid to a dataframe.

Usage

```
textgrid_to_df(file_name)
```

Arguments

file_name	string with a filename or path to the TextGrid

Value

a dataframe with columns: id, time_start, time_end (if it is an interval tier – the same as the start value), content, tier, tier_name and source

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
textgrid_to_df(system.file("extdata", "test.TextGrid",
  package = "phonfieldwork"
))

# this is and example of reading a short .TextGrid format
textgrid_to_df(system.file("extdata", "test_short.TextGrid",
  package = "phonfieldwork"
))
```

---

tier_to_df *TextGrid's tier to dataframe*

Description

Convert selected tier from a Praat TextGrid to a dataframe.

Usage

```
tier_to_df(file_name, tier = 1)
```

Arguments

file_name	string with a filename or path to the TextGrid
tier	value that could be either ordinal number of the tier either name of the tier. By default is '1'.

Value

a dataframe with columns: id, time_start, time_end, content, , tier_name

Author(s)

George Moroz <agricolamz@gmail.com>

Examples

```
tier_to_df(system.file("extdata", "test.TextGrid",
  package = "phonfieldwork"
))
tier_to_df(
  system.file("extdata", "test.TextGrid",
    package = "phonfieldwork"
  ),
  "intervals"
)
```

Index

add_leading_symbols, 3
annotate_textgrid, 3
audacity_to_df, 4

concatenate_soundfiles, 5
concatenate_textgrids, 6
create_empty_textgrid, 7
create_glossed_document, 8
create_image_look_up, 9
create_presentation, 10
create_sound_play, 11
create_subannotation, 12
create_viewer, 13

df_to_eaf, 14
df_to_exb, 15
df_to_tier, 16
draw_sound, 17
draw_spectrogram, 20

eaf_to_df, 22
exb_to_df, 23
extract_intervals, 24

flextext_to_df, 25
formant_to_df, 25

get_sound_duration, 26
get_textgrid_names, 27

intensity_to_df, 27

pitch_to_df, 28

read_from_folder, 29
remove_textgrid_tier, 29
rename_soundfiles, 30

set_textgrid_names, 31
srt_to_df, 32

textgrid_to_df, 32
tier_to_df, 33