

Package ‘prettyB’

October 14, 2022

Type Package

Title Pretty Base Graphics

Version 0.2.2

Maintainer Colin Gillespie <csgillespie@gmail.com>

Description Drop-in replacements for standard base graphics functions. The replacements are prettier versions of the originals.

License GPL-2 | GPL-3

URL <https://github.com/jumpingrivers/prettyB/>

BugReports <https://github.com/jumpingrivers/prettyB/issues>

Imports graphics, grDevices, stats

Suggests covr, knitr, lintr, rmarkdown, testthat, vdiff

VignetteBuilder knitr

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

NeedsCompilation no

Author Colin Gillespie [aut, cre]

Repository CRAN

Date/Publication 2021-02-10 13:50:03 UTC

R topics documented:

prettyB-package	2
add_x_axis	2
barplot.prettyB	3
boxplot.prettyB	5
hist.prettyB	6
plot.prettyB	8
reset_prettyB	9

Index	10
--------------	-----------

prettyB-package

The prettyB package

Description

Anyone who uses R Base graphics, have a 100 and 1 tweaks that they use to make the figures more presentable. This package aims to capture the tweaks in one place. By masking_standard plotting functions, we can automatically make base graphics a bit more pretty.

Author(s)

<csgillespie@gmail.com>

See Also

<https://github.com/jumpingrivers/prettyB>

add_x_axis

Add tick marks to x/y axis A nicer set of default tick marks

Description

Add tick marks to x/y axis

A nicer set of default tick marks

Usage

```
add_x_axis(ticks_x, labels = ticks_x, tick = TRUE, lwd = 0, lwd.ticks = 1)
```

```
add_y_axis(ticks_y, labels = ticks_y, tick = TRUE, lwd = 0, lwd.ticks = 1)
```

Arguments

ticks_x	location of x tick mark
labels	tick label
tick	Display tick mark
lwd	width of line
lwd.ticks	width of tick mark
ticks_y	location of y tick mark

barplot.prettyB	<i>PrettyB barplot.default function</i>
-----------------	-----------------------------------------

Description

This function overrides the default arguments. See `?graphics::barplot.default`

Usage

```
## S3 method for class 'prettyB'
barplot(
  height,
  width = 1,
  space = NULL,
  names.arg = NULL,
  legend.text = NULL,
  beside = FALSE,
  horiz = FALSE,
  density = NULL,
  angle = 45,
  col = NULL,
  border = par("fg"),
  main = NULL,
  sub = NULL,
  xlab = NULL,
  ylab = NULL,
  xlim = NULL,
  ylim = NULL,
  xpd = TRUE,
  log = "",
  axes = TRUE,
  axisnames = TRUE,
  cex.axis = par("cex.axis"),
  cex.names = par("cex.names"),
  inside = TRUE,
  plot = TRUE,
  axis.lty = 0,
  offset = 0,
  add = FALSE,
  args.legend = NULL,
  ...
)

barplot_p(
  height,
  width = 1,
  space = NULL,
```

```

names.arg = NULL,
legend.text = NULL,
beside = FALSE,
horiz = FALSE,
density = NULL,
angle = 45,
col = NULL,
border = par("fg"),
main = NULL,
sub = NULL,
xlab = NULL,
ylab = NULL,
xlim = NULL,
ylim = NULL,
xpd = TRUE,
log = "",
axes = TRUE,
axisnames = TRUE,
cex.axis = par("cex.axis"),
cex.names = par("cex.names"),
inside = TRUE,
plot = TRUE,
axis.lty = 0,
offset = 0,
add = FALSE,
args.legend = NULL,
...
)

```

Arguments

height, width, space
 See ?graphics::barplot.default

names.arg, legend.text, beside
 See ?graphics::barplot.default

horiz, density, angle, col
 See ?graphics::barplot.default

border, main, sub, xlab, ylab
 See ?graphics::barplot.default

xlim, ylim, xpd, log, axes
 See ?graphics::barplot.default

axisnames, cex.axis, cex.names
 See ?graphics::barplot.default

inside, plot, axis.lty
 See ?graphics::barplot.default

offset, add, args.legend
 See ?graphics::barplot.default

... See ?graphics::barplot.default

Examples

```
barplot(VADeaths)
```

boxplot.prettyB	<i>PrettyB boxplot.default function</i>
-----------------	-----------------------------------------

Description

This function overrides the default arguments. See `?graphics::boxplot.default`

Usage

```
## S3 method for class 'prettyB'  
boxplot(  
  x,  
  ...,  
  range = 1.5,  
  width = NULL,  
  varwidth = FALSE,  
  notch = FALSE,  
  outline = TRUE,  
  names,  
  plot = TRUE,  
  border = par("fg"),  
  col = NULL,  
  log = "",  
  pars = list(boxwex = 0.8, staplewex = 0.5, outwex = 0.5),  
  horizontal = FALSE,  
  add = FALSE,  
  at = NULL  
)  
  
boxplot_p(  
  x,  
  ...,  
  range = 1.5,  
  width = NULL,  
  varwidth = FALSE,  
  notch = FALSE,  
  outline = TRUE,  
  names,  
  plot = TRUE,  
  border = par("fg"),  
  col = NULL,  
  log = "",  
  pars = list(boxwex = 0.8, staplewex = 0.5, outwex = 0.5),
```

```

horizontal = FALSE,
add = FALSE,
at = NULL
)

```

Arguments

```

x, ..., range, width
    See ?graphics::boxplot.default
varwidth, notch, outline
    See ?graphics::boxplot.default
names, plot, border
    See ?graphics::boxplot.default
col, log, pars
    See ?graphics::boxplot.default
horizontal, add, at
    See ?graphics::boxplot.default

```

```
hist.prettyB
```

```
PrettyB hist.default function
```

Description

This function overrides the default arguments. See `?graphics::hist.default`

Usage

```

## S3 method for class 'prettyB'
hist(
  x,
  breaks = "Sturges",
  freq = NULL,
  probability = !freq,
  include.lowest = TRUE,
  right = TRUE,
  density = NULL,
  angle = 45,
  col = NULL,
  border = NULL,
  main = paste("Histogram of", xname),
  xlim = range(breaks),
  ylim = NULL,
  xlab = xname,
  ylab,
  axes = TRUE,
  plot = TRUE,
  labels = FALSE,

```

```
    nclass = NULL,  
    warn.unused = TRUE,  
    ...  
)  
  
hist_p(  
  x,  
  breaks = "Sturges",  
  freq = NULL,  
  probability = !freq,  
  include.lowest = TRUE,  
  right = TRUE,  
  density = NULL,  
  angle = 45,  
  col = NULL,  
  border = NULL,  
  main = paste("Histogram of", xname),  
  xlim = range(breaks),  
  ylim = NULL,  
  xlab = xname,  
  ylab,  
  axes = TRUE,  
  plot = TRUE,  
  labels = FALSE,  
  nclass = NULL,  
  warn.unused = TRUE,  
  ...  
)
```

Arguments

x, *breaks*, *freq*, *probability*
See ?graphics::hist.default
include.lowest, *right*, *density*
See ?graphics::hist.default
angle, *col*, *border*, *main*
See ?graphics::hist.default
xlim, *ylim*, *xlab*, *ylab*, *axes*, *plot*
See ?graphics::hist.default
labels, *nclass*, *warn.unused*
See ?graphics::hist.default
... See ?graphics::hist.default

Examples

```
x = rlnorm(100)  
hist(x)
```

`plot.prettyB`*PrettyB plot.default function*

Description

This function overrides the default arguments. See `?graphics::plot.default`

Usage

```
## S3 method for class 'prettyB'
plot(
  x,
  y = NULL,
  type = "p",
  xlim = NULL,
  ylim = NULL,
  log = "",
  main = NULL,
  sub = NULL,
  xlab = NULL,
  ylab = NULL,
  ann = par("ann"),
  axes = TRUE,
  frame.plot = axes,
  panel.first = NULL,
  panel.last = NULL,
  asp = NA,
  ...
)

plot_p(
  x,
  y = NULL,
  type = "p",
  xlim = NULL,
  ylim = NULL,
  log = "",
  main = NULL,
  sub = NULL,
  xlab = NULL,
  ylab = NULL,
  ann = par("ann"),
  axes = TRUE,
  frame.plot = axes,
  panel.first = NULL,
  panel.last = NULL,
  asp = NA,
```



```
    ...
  )
```

Arguments

x, y, type, log See ?graphics::plot.default
 xlim, ylim See ?graphics::plot.default
 main, sub, xlab, ylab See ?graphics::plot.default
 ann, axes See ?graphics::plot.default
 frame.plot, panel.first, panel.last See ?graphics::plot.default
 asp See ?graphics::plot.default
 ... See ?graphics::plot.default

Examples

```
plot_p(1:10, 1:10)
```

```
reset_prettyB
```

```
Set up par and palette Sets up par and palette
```

Description

Set up par and palette
 Sets up par and palette

Usage

```
reset_prettyB()
setup_prettyB()
```

Index

* package

prettyB-package, 2

add_x_axis, 2

add_y_axis (add_x_axis), 2

barplot.prettyB, 3

barplot_p (barplot.prettyB), 3

boxplot.prettyB, 5

boxplot_p (boxplot.prettyB), 5

hist.prettyB, 6

hist_p (hist.prettyB), 6

plot.prettyB, 8

plot_p (plot.prettyB), 8

prettyB (prettyB-package), 2

prettyb (prettyB-package), 2

prettyB-package, 2

reset_prettyB, 9

setup_prettyB (reset_prettyB), 9